
1. Product and Company Identification

Identity (as used on label & list): **All Fleet Motor Oil SAE 15W-40**
Product Description: Base Oil and Additives
Intended Use: Motor Oil

Baum's Castorine Co., Inc.
200 Matthew Street
Rome, N.Y. 13440

Telephone Number: (315) 336-8154
Preparer: Paul Berger
Date Prepared: May 9, 2015

2. Hazards Identification

GHS Signal Word: None

GHS Classifications: Environmental, Hazards to the aquatic environment - Chronic, 3

GHS Phrases: H412 - Harmful to aquatic life with long lasting effects

This product contains hazardous material as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

3. Composition/ Information on Ingredients

Chemical Name	Percentage	CAS #.
Petroleum, solvent refined light paraffinic oil	80 – 90	64741-89-5
Additives	5 – 10	Proprietary
Hazardous and/or Regulated		
Zinc alkyldithiophosphate	< 5	Proprietary

4. First Aid Measures

Inhalation: If symptoms develop, move victim to fresh air.
If symptoms persist, obtain medical attention

Skin Contact Wash with soap and water.

Remove contaminated clothing and wash before reuse.
Get medical attention if needed.

Eye Contact: Flush with water for several minutes.
If effects occur, consult a physician.

Ingestion: Rinse mouth with water.
If symptoms develop, obtain medical attention.

5. Fire Fighting Measures

Flash Point: 176.7 C (350.1 F)

Flash Point Method: COC

Use dry powder, foam, or carbon dioxide fire extinguishers.

Water may be ineffective in fighting an oil fire unless used by experienced fire fighters

6. Accidental Release Measures

Contain spilled material.
Collect in suitable and properly labeled containers.
Pick up excess with inert absorbent material
Keep away from drains and ground water.

7. Handling and Storage

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Keep away from sources of ignition.
Handle with care and avoid spillage on the floor (slippage).

Storage Requirements: Keep away from sources of ignition

8. Exposure Controls/ Personal Protection

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment: Use of safety glasses and gloves are recommended

9. Physical and Chemical Properties

Physical State	Liquid
Appearance, Color	Amber
Solubility	Nil in water
Specific Gravity/Density (Water=1)	0.887
Viscosity	6 cSt at 100 degrees C
Freezing/Melting Pt	-32 F (pour point)

10. Stability and Reactivity

Chemical Stability: Product is Stable under normal conditions

Conditions to Avoid: High temperatures and open flame.

11. Toxicological Information

Repeated skin contact with this product may cause dermatitis or an oil acne.
No test data available on product.
No component is listed as a carcinogen, mutagen, or teratogen.
LD50 / LC50 - No data available

12. Ecological Information

Avoid exposing to the environment, no specific aquatic data available.

13. Disposal Considerations

Disposal of in accordance with local regulations.
Do not flush to surface water or drains.

14. Transport Information

Not regulated by DOT.

15. Regulatory Information

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16. OTHER INFORMATION

The information on this SDS reflects the latest information that we have on hazards, properties, and handling of this product under recommended conditions of use. This company believes this information to be accurate and reliable however, the accuracy and completeness is not guaranteed.